



Care Instructions

RCT

for Sianol Premium protected floors

For initial cleaning and ongoing maintenance of impregnated concrete blocks, we recommend the following procedure:

Initial cleaning

Since it is difficult to estimate the absorption capacity of the substrate during impregnation, a little too much is usually applied. This slight excess is removed without difficulty during initial cleaning. For this purpose, we recommend a maintenance cleaner with a good cleaning effect (GISBAU code: GU 50) in a dilution of 1:20. The diluted cleaner is applied to the pre-wetted floor, left to act for a short time, scrubbed, the cleaning solution is taken up again with a sponge or joint rubber and washed with clear water. For large surfaces, the process can be carried out with an automatic cleaning machine.

Maintenance cleaning

Floors protected with SIANOL PREMIUM facilitate cleaning, because the substrate:

- does not absorb the washing water
- the dirt is only very slowly absorbed by the substrate;
- the dirt does not form a firm adhesion to the substrate.

Consequently, a neutral maintenance cleaner (Cleaner P; GISBAU code: GU 50), which dries without leaving any residues, is sufficient for ongoing maintenance. This means that the cleaner must be neither acidic nor alkaline, must not contain a high proportion of solvents in the application solution and must not contain any substances that build up layers (waxes, etc.) in order to maintain the beneficial properties of the impregnation for a long time.

For manual cleaning, a dilution of the cleaner of approx. 1:200 is recommended. This means to add 50 ml of cleaner to 10 l of cleaning water and to mop the floor with it. Due to the shorter exposure time for automatic cleaning, the dilution can be changed to 1:100 (for heavy soiling to 1:50).

Cleaner P

Neutral maintenance cleaner

- with good cleaning effect
- suitable for the automatic cleaning machine
- with alcohol, dries quickly and without streaks
- without skin-resorptive substances

Field of application

For maintenance cleaning of water-resistant surfaces and floor coverings. Especially recommended for stone, ceramics and tiles.

Dosage

Manually: 50 ml/10 l cold water Machine: 150 ml / 10 l cold water

Ingredients

<5% anionic surfactants, <5% non-ionic surfactants. Other ingredients: alcohol, auxiliaries, fragrances, colorants.

Information

No labeling obligation according to EC directives.

Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label.