



FORMWORK WAX



Pasty release wax for architectural concrete

Product description

FORMWORK WAX is a paste-like, environmentally friendly release wax.

Areas of application

FORMWORK WAX is one of the most universal and economical release agents. It is suitable for heated and unheated concretes, vertical or horizontal demolding, wooden, steel or plastic formwork, white or gray concrete, colored concretes, concrete base surfaces, etc.

Application advantages

Our FORMWORK WAX forms a thin, highly resistant wax layer on the formwork, which promotes the spreading of the concrete and counteracts the formation of pores. It is also suitable for use with complicated forms.

FORMWORK WAX can be used even for construction sites and bridges. The adhesion of plasters and paints is not affected if the technical instructions are followed.

Processing instructions

FORMWORK WAX is applied very sparingly to the formwork in a thin layer. A clean rag, a kind of buffing tool or a floor polisher is best suited for this purpose.

Due to its relatively low melting point, the product softens at higher temperatures. However, this in no way negatively affects the release properties of the product. On the contrary, the processability or yield of the product is increased.

Properties

- Pasty, non-sticky yellowish wax
- Melting point: $35 \pm 5^\circ\text{C}$
- WGK 1 (self-classification)
- Insoluble in water

Consumption

Depending on the desired application approx. 8 g/m^2 .

Packaging

5 l container

Storage

Best stored in a cool place. Otherwise no special requirements.

Shelf life

Five years from date of manufacture in closed original packaging.

Safety

See EC safety data sheet.

Environment

The container can be emptied of all residues and recycled or disposed of according to type.